

# POLYMIX

---

## Acrylic emulsion bonding agent

### Uses

To increase bonding strength of tiles and stone while working at height and external wall

### Advantages

□ Provides excellent bond to concrete, masonry, stonework, plaster and blockboard . it will be used to increase bonding strength for tiles and stone to substrate if we add 2.5 lit poly mix to 25kgs tile adhesive bags.

### Standard compliance

BS 6920

### Properties

Adhesion to concrete – Slant shear bond test (BS 6319 Part 4, 1984)

Control-- -----→ 5.0N/mm<sup>2</sup>

Typical result with POLYMIX -----→20.0N/mm<sup>2</sup>

Curing efficiency (BS 7542: 1992)---→ 85%

### Supply

POLYMIX Supply in 5 & 20 ltr cans

# POLYMIX



**REDWOP CHEMICALS PVT. LTD.**

**OFFICE:**

1<sup>ST</sup> FLOOR SURYACHANDRA COMPLEX,  
NR. K.K.V. HALL, OPP PUNJAB  
HONDA SHOWROOM, KALAWAD ROAD,  
PIN NO.- 360005  
RAJKOT (GUJ.)INDIA.

**FACTORY:**

NR. JAY INTERNATIONAL SCHOOL, OPP  
ARYA BHAGWATI SOCIETY,  
KALAWAD ROAD,  
AT. CHHAPRA(VILLE.)  
METODA G.I.D.C.  
DIST. RAJKOT (GUJ.)INDIA.

W.: [www.redwopchemical.com](http://www.redwopchemical.com)

e.: [admin@redwopchemical.com](mailto:admin@redwopchemical.com)

Ph. +91 281 2576664

Customer care: +91 97246 55551

**NOTE:**Redwop products are guaranteed against defective materials and manufacture and are sold subject to its standard terms & condition of sales,



ISO 9001:2008

